

# DCNM-DE

www.bo h t . o



u 4.3

u

u

S

S

S

S

S

4.3

4.3

—

—

—

•

•

•

•

•

•

•

S

•

• 4.3

—

—

•

( )

•

—

• 4.3

•

—

—

•

-  
-  
-  
-

- 
- 
- 3. 0. 4
- 2 J4
- 

**DECLARATION OF CONFORMITY**

|    |                 |
|----|-----------------|
| /  |                 |
| CE | DECL EC DCNM-DE |

**DECLARATION OF CONFORMITY**

|   |                  |
|---|------------------|
| 1 | DCNM DE DICENTIS |
|---|------------------|

**DECLARATION OF CONFORMITY**

|     |                       |
|-----|-----------------------|
|     | 48 VDC                |
|     | 5 W                   |
|     | 100 Hz – 20 kHz -3 dB |
| THD | < 0.1 %               |
|     | > 90 dB               |
|     | > 90 dB               |

|  |        |          |
|--|--------|----------|
|  | 80 dB  | IEC60914 |
|  | 110 dB | IEC60914 |

|  |                  |     |
|--|------------------|-----|
|  | 72 dB            | 0.5 |
|  | 87 dB            |     |
|  | 0 dBV            |     |
|  | 3 dBV            |     |
|  | > 32 ohm< 1k ohm |     |
|  | 65 mW            |     |

|     |   |     |
|-----|---|-----|
|     | 109.22  | 4.3 |
| NFC | ISO/IEC14443<br>A 106 kbps 848 kbps<br>MIFARE 106kbps |     |

|     |  |
|-----|--|
| x x | 72 x 259 x 139<br>2.8 x 10.2 x 5.5<br>(RAL 9017) |
|-----|--|

|  |      |     |
|--|------|-----|
|  | 1035 | 2.3 |
|--|------|-----|

|  |                              |
|--|------------------------------|
|  | 5 °C +45 °C<br>41 °F +113 °F |
|--|------------------------------|

|  |                                 |
|--|---------------------------------|
|  | -30 °C +70 °C<br>-22 °F +158 °F |
|--|---------------------------------|

|  |        |      |
|--|--------|------|
|  | < 90 % | > 5% |
|--|--------|------|

**DECLARATION OF CONFORMITY**

|                |   |
|----------------|---|
| DCNM-DE<br>4.3 | S |
|----------------|---|

|         |  |
|---------|--|
| DCNM-DE |  |
|---------|--|

|                 |   |   |
|-----------------|---|---|
| DCNM-HDMIC      | S | S |
| S<br>DCNM-HDMIC |   |   |

|                |   |   |
|----------------|---|---|
| DCNM-MICS      | S | S |
| S<br>DCNM-MICS |   |   |

|                |   |   |
|----------------|---|---|
| DCNM-MICL      | S | S |
| S<br>DCNM-MICL |   |   |

|           |    |         |   |
|-----------|----|---------|---|
| DCNM-TCDD | 10 | DCNM-xD | 0 |
| 0         | 0  | S       | 0 |
| DCNM-TCDD |    |         |   |

|             |               |     |       |
|-------------|---------------|-----|-------|
| ACD-MFC-ISO | MIFAREclassic | 1kB | 50pcs |
| 2           |               | 0   | /     |
| ACD-MFC-ISO |               |     |       |

ACD-EV1-ISO MIFARE EV1 8kB 50pcs  
 S 2 V 0 /

ACD-EV1-ISO

---

DCNM-LSSL S S S  
 S  
 SYS  
 DCNM-LSSL

---

DCNM-LSVT S S  
 S S  
 S S

---

DCNM-LSID S S S S  
 S S  
 S S  
 S  
 DCNM-LSID

---

DCNM-LSDU 2 S S  
 S S S  
 S S  
 DCNM-LSDU

---