

LBB 451x/00 Integrus

www.boschsecurity.com.cn

u LBB 4511/00	1300	4
u LBB 4512/00	2600	4
u	(IRED)	

u
u

•

- HF 2 x BNC

1 LBB 451x/00 Integrus
 1
 1
 2

	100-240Vac 50-60Hz
LBB 4511	100W
LBB 4511	8W
LBB 4512	180W

-
-
- LED
-
-
-
-
-
- IRED
-
- 2 LED
- 2 LED
- LED LED
- LED LED
-

LBB 4512	10W
IRED	
LBB 4511	260
LBB 4512	480
LBB 4511	12 W/sr
LBB 4512	24 W/sr
	± 22°
HF	1 Vpp 10mVpp

	<ul style="list-style-type: none"> • • M10 1/2 • • (LBB 3414/00) •
x x	
LBB 4511	200x500x175 7.9x19.7x6.9
LBB 4512	300x500x175 11.0x19.7x6.9
	0 15 30°
/	0 15 30 45 60 75 90°
LBB 4511	6.8 15
LBB 4511	7.6 17
LBB 4512	9.5 21
LBB 4512	10.3 23

LBB 4512/00-US Integrus (US)
Integrus 2600
27986
LBB4512/00-US

LBB 3414/00
LBB 3414/00
LBB3414/00

INT-FCRAD
1 INT-FCRAD
INT-FCRAD

LBB 4511/00 Integrus
Integrus 1300
13993
LBB4511/00

LBB 4512/00 Integrus
Integrus 2600
27986
LBB4512/00

LBB 4511/00-US Integrus (US)
Integrus 1300
13993
LBB4511/00-US

:

:

333
: 200335
: +86 21 22181111
: +86 21 22182388
www.boschsecurity.com.cn

11 5
506-509
: +852 2635 2815
: +852 2648 7986
www.boschsecurity.com.cn