

GLX-D® Advanced

GLX-D ADVANCED

UA846Z2 GLX-D



/

GLXD4R

2.4 GH

GLXD4R

LED

LCD

XLR ¼



GLXD1
GLXD2

GLXD4R

GLXD1
GLXD2

SM58

30 60
20 50
16



GLX-D A 1

GLX-D

1. GLX-D

GLXD4R

2.4 GH



2. GLX-D

(11)

A 1

9

GLX-D



PA805Z2-RSMA

8 B

2.4GH

24 B



UA505

PA805Z2-RSMA UA8-Z2



RSMA

50

6 25 50 100

3.

GLX-D

4.

GLX-D

USB



16





GLX-D A 1

	UA846Z2	GLXD4R	PA805Z2-RSMA
9 11	15 VDC	42 × 197 × 163 (× ×)	<2.1 (VSWR) 2050 2700 MH
30 (100) 60 (200) 20 (65) 50 (165)	15 VDC (× 6)	907.2	(2.45 GH) 8 B
GLX-D	18 C 63 C(0 F 145 F)	14 18 VDC()550 A	3 dB 100
20 H 20 kH	45 × 483 × 192 (× ×)	>35 B()	(2.45 GHz) 89%
120 B A	1.63	18 42 B(1 B)	50
1 /A 4.0 2 3 4 /B 7.3	SMA	/ 30 B	(2.45 GHz) 24 B
-88 B ()	2400 2483.5 MH	50	SMA
0.2%()	35 B()	½	105 × 164 × 27.5 (× ×)
10 W E.I.R.P.()	50	20 B	70
18 C(0 F) 57 C(135 F)	10 B		
29 C(20 F) 74 C(165 F)	+15 B		
() 3)	WA302 SMA 2400 2483.5 MH (OIP3) 48 B ()		
16	50		
/	35 B()		
	3 0 B		

		6.35 (1/4)
	100	100 (50)
	+18 BV 12 BV	+12 BV
	1= 2= 3=	= = =

GLXD1		GLXD2	
90.4 × 64.5 × 22.9 (× ×)	(1 kH 1%)+	(SM58) 252 × 51 (×)	10 W E.I.R.P.()
3.7 V	8.4 BV (7.5 V -)	(SM58) 267	145 B SPL
900 k	TA4M 1 ()	3.7 V	
10 W E.I.R.P.()	2 +5V		
4 (TA4M)	3 4 (4)		



625 22
info@shure.com.hk

618
(II) 18 A
info@shure.com.cn

1
816