

- ▶ 12”
- ▶ 1.5”
- ▶
- ▶ DuraFlex™
- ▶ 70° × 60° (H × V)
- ▶ 16
- ▶
- ▶ 13

- ▶
- ▶
- VPX712M 12”
- VPX712M 1.5”  
12”
- 12”
- 70° × 60° (H × V)
- VPX712M
- VPX712M
- Speakon®NL-4
- 0° 10° 13  
35mm

DuraFlex™

16

13

12”

70° × 60° (H × V)

12”

15/18 mm

M10

35mm

Neutrik®

18 Kg (39.7 lbs)

(-10 dB) <sup>1</sup>	50 Hz - 20 kHz
(±3 dB) <sup>1</sup>	85 Hz - 20 kHz
	70° × 60° (H × V)
	2.2 kHz
<sup>1</sup>	400 W/800 W/1600 W ( / / )
(1w@1m) <sup>2</sup>	97 dB
	8 Ohms
<sup>3</sup>	123 dB (129 dB )
	1 × 12” (304.8 mm)
	1 × JBL 2408H-2
	15/18 mm
	13 × (3@ 3@ 2@ 3@ ) M10
	35mm
	1 × ( )
	DuraFlex™
	16
	2 × Neutrik®Speakon®NL-4 ( )
(H × W × D)	636 mm × 381 mm × 344 mm (25.0 in × 15.0 in × 13.5 in)
	18 Kg (39.7 lbs)
	SS2-BK
	SS3-BK

1 IEC 6 dB 2  
2 (4 )  
3

VPX712M

